Printing date 18.03.2014

Revision: 03.16.2015

1 Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
 Trade name: Seal-Krete High Performance Epoxy Shell WB250 Part A
 Article number: 510001, 518001, 519001, 521001, 522001, 524001, 525001, 541001, 544001, 547001, 55001, 555001, 555001, 557001, 558001, 559991, 560001, 521808, 550801, 559898, 560808 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 Application of the substance / the mixture Epoxy coating
 1.3 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: Seal-Krete / Clayton Corporation 306 Gandy Road Auburndale, FL 33823 Phone: 863-967-1535 Toll-Free: 1-800-323-7357
• 1.4 Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585
2 Hazards identification
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H227. H227: Combustible Liquid. (General GHS and USA only)
Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation.
Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xi; Irritant R36: Irritating to eyes.
 Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Classification system:
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.
· 2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008 H227: Combustible Liquid. (General GHS and USA only) (Contd. on page 2)

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy S	Shell WB250 Part A
regulation: H411.	Contd. of page) azard Statements are applicable only to the EU regulations and not the US GH ssified and labelled according to the CLP regulation.
· Hazard pictogram	
$\langle \mathbf{\hat{t}} \rangle$	
GHS07	
· Signal word Warr	ning
 Hazard statement 	ts
H315 Causes skin	irritation.
H319 Causes serie	ous eye irritation.
 Precautionary sta 	atements
P280	Wear protective gloves / eye protection.
P261	Avoid breathing mist/vapours/spray.
P305+P351+P338	3 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
· Hazard description	
· WHMIS-symbols:	
-	ial causing other toxic effects
$\mathbf{}$	J J J J J J J J J J J J J J J J J J J
· NFPA ratings (sc	
Health	
Fire = 1	
Reactiv	ity = 0
· HMIS-ratings (sca	ale 0 - 4)
HEALTH 0 Health	$\mathbf{n} = 0$
FIRE 1 Fire =	
Reactivity 0 React	iivity = 0
	g term health hazard from repeated or prolonged exposures.
 HMIS Long Term 	Health Hazard Substances
13463-67-7 titaniu	
2.3 Other hazards	
	nd vPvB assessment
 Results of PBT all 	
Results of PBT and PBT: Not applicable	

(Contd. on page 3)

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part A

(Contd. of page 2)

3.2 Mixtures Description: Mixture of subst	tances listed below with nonhazardous additions.	
Dangerous components:		
	Polyamine amides blend with acidic polyesters Xi R36/38; Xi R43 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide substance with a Community workplace exposure limit	10-20%
CAS: 7631-86-9 EINECS: 231-545-4	silicon dioxide	< 2,0%
CAS: 1344-28-1 EINECS: 215-691-6	aluminium oxide substance with a Community workplace exposure limit	< 2,0%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0	2,4,6-tris(dimethylaminomethyl)phenol C R34; Xn R22 R52/53 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302 Aquatic Chronic 3, H412	< 2,0%

4 First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- Do not pull solidified product off the skin.
- If skin irritation continues, consult a doctor.
- · After eye contact:
- Immediately remove contact lenses if possible.
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing:
- Rinse out mouth and then drink plenty of water.
- Do not induce vomiting; call for medical help immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- Coughing Breathing difficulty
- Nausea
- Cramp
- · Hazards
- Danger of disturbed cardiac rhythm.
- Condition may deteriorate with alcohol consumption.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part A

4.3 Indication of any immediate medical attention and special treatment needed

If necessary oxygen respiration treatment.

Monitor circulation, possible shock treatment.

Medical supervision for at least 48 hours.

Later observation for pneumonia and pulmonary oedema.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

- Wear fully protective suit.
- · Additional information No further relevant information available.

6 Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources. · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. • 6.3 Methods and material for containment and cleaning up: Allow to solidify. Pick up mechanically. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. · 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

- Use only in well ventilated areas.
- Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part A

• Information about fire - and explosion protection: No special measures required.

 \cdot 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

 \cdot Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 13463-67-7 titanium dioxide PEL (USA) Long-term value: 15* mg/m³ *total dust REL (USA) See Pocket Guide App. A TLV (USA) Long-term value: (10) NIC-1* mg/m³ *respirable fraction, NIC-A3 Long-term value: 10 mg/m³ EL (Canada) IARC 2B Long-term value: 10 mg/m³ EV (Canada) total dust 1344-28-1 aluminium oxide Long-term value: 15*; 15** mg/m³ PEL (USA) *Total dust; ** Respirable fraction Long-term value: 10* 5** mg/m³ REL (USA) *Total dust **Respirable fraction TLV (USA) Long-term value: 1* mg/m³ as AI; *as respirable fraction EL (Canada) Long-term value: 10 mg/m³ EV (Canada) Long-term value: 10 mg/m³ total dust • DNELs No further relevant information available. PNECs No further relevant information available. • Additional information: The lists valid during the making were used as basis. (Contd. on page 6)

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part A

(Contd. of page 5) 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required under normal conditions of use. For spills, respiratory protection may be advisable. Use suitable respiratory protective device when aerosol or mist is formed. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR Butvl rubber, BR · Eye protection: Safety glasses Body protection: Protective work clothing Limitation and supervision of exposure into the environment No further relevant information available. Risk management measures See Section 7 for additional information. No further relevant information available. (Contd. on page 7)

Printing date 18.03.2014

Trade name: Epoxy Shell WB250 Part A

9 Physical and chemical prope	erties	
9.1 Information on basic physical a General Information	and chemical properties	
 Appearance: Form: Colour: 	Liquid Clear Whitish	
 Odour: Odour threshold: 	Mild Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not Determined. Undetermined.	
· Flash point:	190 °F / 89 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Auto/Self-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not self-igniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
 Explosion limits: Lower: Upper: 	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1,094 g/cm ³ (9.114 Lbs/gal) Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.	
 Solvent content: Organic solvents: VOC (US EPA Method 24) 	27 % wt (270 g/L) 27 % wt (270 g/L)	
Solids content:	Not determined.	(Contd. on page 8)

Revision: 03.16.2015

(Contd. of page 6)

Printing date 18.03.2014

Revision: 03.16.2015

(Contd. of page 7)

Trade name: Epoxy Shell WB250 Part A

• 9.2 Other information

No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions
- Toxic fumes may be released if heated above the decomposition point.
- Reacts with strong acids and oxidizing agents.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Sensitizing effect by skin contact is possible by prolonged exposure.
- Additional toxicological information:

Toxic and/or corrosive effects may be delayed up to 24 hours.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

Danger through skin adsorption.

- · Sensitisation: Sensitization possible by skin contact.
- Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- 12.2 Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 9)

Printing date 18.03.2014

Trade name: Epoxy Shell WB250 Part A

Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· 14.1 UN-Number		
· DOT, ADR, ADN, IMDG, IATA	Not Regulated	
 14.2 UN proper shipping name 		
· DOT, ADR, ADN, IMDG, IATA	Not Regulated	
 14.3 Transport hazard class(es) 		
· DOT, ADR, ADN, IMDG, IATA		
Class	Not Regulated	
 14.4 Packing group 	-	
· DOT, ADR, IMDG, IATA	Not Regulated	
 14.5 Environmental hazards: 		
Marine pollutant:	No	
 14.6 Special precautions for user 	Not applicable.	
14.7 Transport in bulk according to Ann	nex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
 UN "Model Regulation": 	-	

(Contd. on page 10)

Revision: 03.16.2015

(Contd. of page 8)

Printing date 18.03.2014

Trade name: Epoxy Shell WB250 Part A

Revision: 03.16.2015

(Contd. of page 9)

5 Regulatory information	
 15.1 Safety, health and environmental regulations/legislation specific for the subs United States (USA) SARA 	tance or mixtur
 Section 355 (extremely hazardous substances): 	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
1344-28-1 aluminium oxide	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
 Proposition 65 (California): Chemicals known to cause cancer: Reference to Titanium Dioxide is based on unbound respirable particles and is not gene product as supplied. 13463-67-7 titanium dioxide 	erally applicable
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· IARC (International Agency for Research on Cancer)	
13463-67-7 titanium dioxide	21
7631-86-9 silicon dioxide	3
TLV (Threshold Limit Value established by ACGIH)	
13463-67-7 titanium dioxide	A
1344-28-1 aluminium oxide	A
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 titanium dioxide	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	

(Contd. of page 10)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part A

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

7631-86-9 silicon dioxide

1344-28-1 aluminium oxide

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.
- R22 Harmful if swallowed.
- R34 Causes burns.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Sources SDS Prepared by: ChemTel Inc.

(Contd. on page 12)

Printing date 18.03.2014

Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part A

(Contd. of page 11)

1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com