
Revision: 30.10.2012 Printing date 30.10.2012

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A
- · Article number: 243002
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Poly-Shell 7000 is a Polyaspartic coating that is used to seal concrete floors.
- · Application of the substance / the preparation Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:

Seal-Krete / Clayton Corporation 306 Gandy Road

Auburndale, FL 33823 Phone: 863-967-1535 Toll-Free: 1-800-323-7357





ChemTel Inc.

(800)255-3924, +1 (813)248-0585



2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/38: Irritating to eyes and skin.

R10: Flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

(Contd. on page 2)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed. P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P362 Take off contaminated clothing and wash before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Hazard description:
- · WHMIS-symbols:

B3 - Combustible liquid

D2B - Toxic material causing other toxic effects





(Contd. on page 3)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 2)

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1 2 Fire = 2

REACTIVITY Reactivity = 0

- * Indicates a long term health hazard from repeated or prolonged exposures.
- · HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

	Mixed Aspartic Esters	> 50%
	x Xi R38	
	Skin Irrit. 2, H315	
CAS: 98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	
EINECS: 202-681-1	X Xi R36/38	
	R10	
	♦ Flam. Liq. 3, H226	
	Škin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 623-91-6	diethyl fumarate	
EINECS: 210-819-7	X Xn R22	
	Acute Tox. 4, H302	
CAS: 6864-37-5	2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	< 1,0%
EINECS: 229-962-1	😡 T R23/24; 🗾 C R35; 🗙 Xn R22; 🌄 N R51/53	
Index number: 612-110-00-	7 7 10010 10X. 0, 11011, 7 10010 10X. 0, 11001	
	Skin Corr. 1A, H314	
	Aquatic Chronic 2, H411	
	♠ Acute Tox. 4, H302	

· Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. on page 4)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 3)

4 First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Dizziness

Gastric or intestinal disorders

- · Hazards Condition may deteriorate with alcohol consumption.
- · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Monitor circulation.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Hydrogen fluoride (HF)

Nitrogen oxides (NOx)

Carbon monoxide (CÓ)

Hydrogen chloride (HCI)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 5)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 4)

· Additional information Cool endangered receptacles with water haze or fog.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Emergency cooling must be available in case of nearby fire.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Do not store together with acids.

Store away from oxidizing agents.

Store away from foodstuffs.

Store away from reducing agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

(Contd. on page 6)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 5)

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Chloroprene rubber, CR

· Not suitable are gloves made of the following materials: PVA gloves

(Contd. on page 7)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 6)

· Eye protection:

Contact lenses should not be worn.



Safety glasses

Goggles recommended during refilling

- · Body protection: Impervious protective clothing
- · Limitation and supervision of exposure into the environment No special requirements.
- Risk management measures

See Section 7 for additional information.

No special requirements.

9 Physical	and	chemical	properties

· 9.1 Information on basic physical and chemical properties			
General Information			
· Appearance:			
Form:	Liquid		
Colour: · Odour:	Amber coloured Petroleum-like		
· Odour : · Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	Undetermined.		
· Flash point:	App. 54 °C (129 °F)		
· Flammability (solid, gaseous):	Not applicable.		
· Ignition temperature:	Not determined.		
· Decomposition temperature:	Not determined.		
· Self-igniting:	Product is not selfigniting.		
· Danger of explosion:	Product does not present an explosion hazard.		
· Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
· Vapour pressure:	Not determined.		
· Density at 20°C:	1,09 g/cm³ (9.11 lbs/gal)		
Relative density	Not determined.		
· Vapour density	Not determined.		
· Evaporation rate	Not determined.		

(Contd. on page 8)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 7)

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC (EC) 8,3 g/l (EPA Method <u>24)</u>

• 9.2 Other information No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions

Contact with strong acids releases hydrogen fluoride.

Reacts with catalysts, oxidizing agents and strong alkali.

Strong exothermic reaction with acids.

Contact with acids releases toxic gases.

Contact with acids releases irritant gases.

Flammable.

Reacts with strong alkali.

Reacts with peroxides and other radical forming substances.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Halogenated hydrocarbons

Poisonous gases/vapours

Fluorinated hydrocarbons

Hydrogen fluoride

Corrosive gases/vapours

Ammonia

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.

(Contd. on page 9)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 8)

- · on the eye: Irritating effect.
- · Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

Sensitizing effect through inhalation is possible by prolonged exposure.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

12 Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: The product contains materials that are harmful to the environment.
- 12.2 Persistence and degradability The product is partly biodegradale. Significant residuals remain.
- 12.3 Bioaccumulative potential May be accumulated in organism
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

At present there are no ecotoxicological assessments.

This statement was deduced from products with a similar structure or composition.

The decarations are valid for the component with the highest toxicological risk.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

(Contd. on page 10)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 9)

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Disposal must be made according to official regulations.

· Recommended cleansing agents: Solvent naphtha

14 Transport information

· 14.1 UN-Number

• **DOT** UN1993 • **ADR, IMDG, IATA** UN1993

· 14.2 UN proper shipping name



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

·DOT FLAMMABLE LIQUID, N.O.S

(CHLOROBENZOTRIFLUORIDES)

·ADR 1993 FLAMMABLE LIQUID, N.O.S.

(CHLOROBENZOTRIFLUORIDES)

· IMDG, IATA FLAMMABLE LIQUID, N.O.S.

(CHLOROBENZOTRIFLUORIDES)

- · 14.3 Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids.

· Label

· ADR



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

(Contd. on page 11)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

	(Contd. of page 10
· Label	3
· 14.4 Packing group · DOT, ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
14.6 Special precautions for userDanger code (Kemler):EMS Number:	Warning: Flammable liquids. 30 F-E <u>,S-E</u>
· 14.7 Transport in bulk according to Anno MARPOL73/78 and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR · Tunnel restriction code	D/E
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (CHLOROBENZOTRIFLUORIDES), 3, III

15 Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 12)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 11)

· Carcinogenic Categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Canada
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R22 Harmful if swallowed.
- R23/24 Toxic by inhalation and in contact with skin.
- R35 Causes severe burns.
- R36/38 Irritating to eyes and skin.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 13)

Printing date 30.10.2012 Revision: 30.10.2012

Trade name: Seal-Krete Poly-Shell 7000 Low Odor 50 VOC Part A

(Contd. of page 12)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU)