Printing date 08.08.2013

Revision: 08.08.2013

1 Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
<ul> <li>Trade name: Seal-Krete Surface - Shell Part B</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.</li> </ul>
· Application of the substance / the preparation Polymeric floor coating
<ul> <li>1.3 Details of the supplier of the Safety Data Sheet</li> <li>Manufacturer/Supplier: Convenience Products, division of Clayton Corp.</li> <li>866 Horan Drive Fenton, MO 63026-2416 Phone: 636-349-5855</li> </ul>
• <b>1.4 Emergency telephone number:</b> ChemTel Inc. (800)255-3924, +1 (813)248-0585
2 Hazards identification
Classification according to Regulation (EC) No 1272/2008     GHS08 health hazard     Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.     STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
GHS07
Acute Tox. 4H332 Harmful if inhaled.Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.STOT SE 3H335 May cause respiratory irritation.
· Classification according to Directive 67/548/EEC or Directive 1999/45/EC
Xn; Harmful R20: Harmful by inhalation.
R42/43: May cause sensitisation by inhalation and skin contact.
Xi; Irritant
R36/37/38: Irritating to eyes, respiratory system and skin. (Contd. on page 2)

Revision: 08.08.2013

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 08.08.2013

Trade name: Seal-Krete Surface - Shell Part B (Contd. of page 1) · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. **Classification system:** The classification is according to the latest editions of the EU-lists, and extended by company and literature data. The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS07 GHS08 · Signal word Danger Hazard-determining components of labelling: diphenylmethanediisocyanate, isomeres and homologues 4,4'-methylenediphenyl diisocyanate · Hazard statements H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Do not breathe dust/fume/gas/mist/vapours/spray. P260 P285 In case of inadequate ventilation wear respiratory protection. Wear protective gloves/protective clothing/eye protection/face protection. P280 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P302+P352 IF ON SKIN: Wash with plenty of soap and water. Additional information: Contains isocyanates. May produce an allergic reaction. · Hazard description: · WHMIS-symbols: D2A - Very toxic material causing other toxic effects (Contd. on page 3)


Printing date 08.08.2013

Revision: 08.08.2013

# Trade name: Seal-Krete Surface - Shell Part B

(Contd. of page 2)

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH1Health = \*2FIRE1Fire = 1REACTIVITY0Reactivity = 0

\* - Indicates a long term health hazard from repeated or prolonged exposures.

#### · HMIS Long Term Health Hazard Substances

All ingredients are listed.

· 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

#### **3** Composition/information on ingredients · 3.2 Mixtures • Description: Mixture of substances listed below with nonhazardous additions. Dangerous components: CAS: 101-68-8 4.4'-methylenediphenyl diisocyanate 25-75% X Xn R20; X Xn R42/43; X Xi R36/37/38 EINECS: 202-966-0 Index number: 615-005-00-9 Carc. Cat. 3 Resp. Sens. 1, H334; STOT RE 2, H373 🚯 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 25-75% CAS: 9016-87-9 diphenylmethanediisocyanate isomeres and homologues X Xn R20; X Xn R42/43; X Xi R36/37/38 Carc. Cat. 3 Resp. Sens. 1, H334; STOT RE 2, H373 🚯 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335

• Additional information: For the wording of the listed risk phrases refer to section 16.

# 4 First aid measures

#### · 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

(Contd. on page 4)

٦

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 08.08.2013

Г

Revision: 08.08.2013

	(0 · · · · · ·
Do not leave affected persons unattended.	(Contd. of page
In case of irregular breathing or respiratory arrest provide artificial respiration.	
Provide oxygen treatment if affected person has difficulty breathing.	
· After inhalation:	
Take affected persons into fresh air and keep quiet.	
In case of irregular breathing or respiratory arrest provide artificial respiration.	
Seek immediate medical advice.	
In case of unconsciousness place patient stably in side position for transportation.	
· After skin contact:	
Immediately wash with water and soap and rinse thoroughly.	
If skin irritation continues, consult a doctor.	
· After eye contact:	
Immediately remove contact lenses if possible.	
Rinse opened eye for several minutes under running water. Then consult a doctor.	
• After swallowing:	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; call for medical help immediately.	
• 4.2 Most important symptoms and effects, both acute and delayed	
Breathing difficulty	
Asthma attacks	
Dizziness	
Coughing Nausea	
Disorientation	
· Hazards	
Danger of impaired breathing. Danger of pulmonary oedema.	
• 4.3 Indication of any immediate medical attention and special treatment needed	4
Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible	
Contains isocyanates. Consult literature for specific antidotes.	
Medical supervision for at least 48 hours.	
If blue colouring appears (lips, ear-lobes, finger-nails), give oxygen treatment as quic	kiy as possible.
Later observation for pneumonia and pulmonary oedema. Treat skin and mucous membrane with antihistamine and corticoid preparations.	
5 Firefighting measures	
· 5.1 Extinguishing media	
<ul> <li>Suitable extinguishing agents:</li> </ul>	
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant fo	am.
· For safety reasons unsuitable extinguishing agents: None.	
<ul> <li>5.2 Special hazards arising from the substance or mixture</li> </ul>	
During heating or in case of fire poisonous gases are produced.	
· 5.3 Advice for firefighters	
· Protective equipment:	
Wear self-contained respiratory protective device.	
Wear fully protective suit.	
	(Contd. on page s

(Contd. of page 4)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 08.08.2013

Revision: 08.08.2013

#### Trade name: Seal-Krete Surface - Shell Part B

· Additional information Cool endangered receptacles with water fog or haze.

### 6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Additional Spill Procedures/Neutralization: Neutralization solutions:

(1) Colorimetric Laboratories Inc. (CLI) decontamination solution.

(2) A mixture of 75% water, 20% non-ionic surfactant (e.g. Plurafac SL-62, Tergitol TMN-10) and 5% n-propanol.

(3) A mixture of 80% water, 20% non-ionic surfactant (e.g. Plurafac SL-62, Tergitol TMN-10).

(4) A mixture of 90% water, 3-8% ammonium hydroxide or concentrated ammonia, and 2% liquid detergent.

Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

# 7 Handling and storage

• 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Provide ventilation for receptacles. Store in a cool location.
   Avoid storage near extreme heat, ignition sources or open flame. Use only receptacles specifically permitted for this substance/product.
- Information about storage in one common storage facility: Store away from foodstuffs.
   Description and existing and existing metasials

Do not store together with oxidizing and acidic materials.

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Store receptacle in a well ventilated area. Keep container tightly sealed.

(Contd. on page 6)

(Contd. of page 5)

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 08.08.2013

Revision: 08.08.2013

Trade name: Seal-Krete Surface - Shell Part B

• 7.3 Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

8.1 Control p	
•	vith limit values that require monitoring at the workplace:
-	methylenediphenyl diisocyanate
PEL (USA)	Short-term value: C 0,2 mg/m <sup>3</sup> , C 0,02 ppm
REL (USA)	Short-term value: C 0,2* mg/m <sup>3</sup> , C 0,02* ppm
	Long-term value: 0,05 mg/m <sup>3</sup> , 0,005 ppm
	*10-min
TLV (USA)	0,051 mg/m³, 0,005 ppm
EL (Canada)	Short-term value: C 0,01 ppm
	Long-term value: 0,005 ppm
	Skin; S
EV (Canada)	0,005 ppm
<ul> <li>Additional in</li> <li>8.2 Exposure</li> <li>Personal protogram</li> <li>General protogram</li> <li>from foodstuff all soiled and breaks and at Do not inhale</li> </ul>	rther relevant information available. formation: The lists valid during the making were used as basis. e controls tective equipment: ective and hygienic measures: Keep away is, beverages and feed. Immediately remove contaminated clothing. Wash hands before the end of work. gases / fumes / aerosols. with the eyes and skin.
<ul> <li>Respiratory  </li> </ul>	
	bined Organic Vapor and Particulate Respirator is recommended for use during all essing activities.
· Protection of	hands:
Prote	ective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

(Contd. on page 7)

Printing date 08.08.2013

Revision: 08.08.2013

#### Trade name: Seal-Krete Surface - Shell Part B

(Contd. of page 6)

• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:

Contact lenses should not be worn.



Safety glasses

Body protection: Impervious protective clothing

- $\cdot$  Limitation and supervision of exposure into the environment
- No further relevant information available.
- Risk management measures
   Special materials should be readily available for skin exposures and for spills. See Section 4 for skin exposure information, and Section 6 for spill control information.
   See Section 7 for additional information.

No further relevant information available.

9.1 Information on basic physical	and chemical properties	
General Information		
Appearance: Form:	Liquid	
Colour:	Brown	
Odour:	Acrid	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	>500 °F/ >260 °C	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	>500 °F / >260 °C	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion hazard.	
		(Contd. on page

Printing date 08.08.2013

Revision: 08.08.2013

#### Trade name: Seal-Krete Surface - Shell Part B

		(Contd. of page
· Explosion limits:		
Lower:	0,4 Vol %	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1,23 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
<ul> <li>9.2 Other information</li> </ul>	No further relevant information available.	

# 10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions
- Reacts with amines.

Toxic fumes may be released if heated above the decomposition point.

Reacts with catalysts, oxidizing agents and strong alkali.

Contact with acids releases toxic gases.

- Exothermic reaction.
- 10.4 Conditions to avoid Store away from oxidizing agents.
- 10.5 Incompatible materials: Contact with acids liberates toxic gases.
- **10.6 Hazardous decomposition products:** Poisonous gases/vapours

Hydrogen cyanide (prussic acid) Nitrogen oxides Carbon monoxide and carbon dioxide

Isocyanate

(Contd. on page 9)

Printing date 08.08.2013

Revision: 08.08.2013

#### Trade name: Seal-Krete Surface - Shell Part B

(Contd. of page 8)

## **11 Toxicological information**

#### · 11.1 Information on toxicological effects

· Acute toxicity:

#### · LD/LC50 values relevant for classification:

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

- Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

Toxic and/or corrosive effects may be delayed up to 24 hours.

- Danger through skin adsorption.
- Sensitisation: Sensitization possible by inhalation and/or dermal contact.
- **Repeated dose toxicity:** May cause damage to organs through prolonged or repeated exposure . Repeated exposures may result in skin and/or respiratory sensitivity.

#### **12 Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: The material is harmful to the environment.
- 12.2 Persistence and degradability Moderately /partly biodegradable
- 12.3 Bioaccumulative potential Does not accumulate in organisms.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

- The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.
- After neutralization a reduction of the harming action may be recognized
- · Additional ecological information:
- · General notes:

This statement was deduced from products with a similar structure or composition.

Avoid transfer into the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 10)

Printing date 08.08.2013

Revision: 08.08.2013

#### Trade name: Seal-Krete Surface - Shell Part B

(Contd. of page 9)

#### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

#### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

#### · Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
DOT, ADR, ADN, IMDG, IATA	N/A	
14.2 UN proper shipping name DOT, ADR, ADN, IMDG, IATA	N/A	
14.3 Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	N/A	
14.4 Packing group		
DOT, ADR, IMDG, IATA	N/A	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anno	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	

(Contd. on page 11)

Printing date 08.08.2013

Revision: 08.08.2013

# Trade name: Seal-Krete Surface - Shell Part B

(Contd. of page 10)

o nogalati	ory information	
<ul> <li>15.1 Safet</li> <li>United State</li> <li>SARA</li> </ul>	y, health and environmental regulations/legislation specific for the substan ates (USA)	ce or mixtu
· Section 35	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	13 (Specific toxic chemical listings):	
All ingredie	ents are listed.	
· TSCA (To	xic Substances Control Act):	
All ingredie	ents are listed.	
	on 65 (California):	
· Chemicals	s known to cause cancer:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients is listed.	
· Carcinoge	enic Categories	
•	ironmental Protection Agency)	
	diphenylmethanediisocyanate, isomeres and homologues	CBI
101-68-8	4,4'-methylenediphenyl diisocyanate	CBI
· IARC (Inte	ernational Agency for Research on Cancer)	
	diphenylmethanediisocyanate, isomeres and homologues	
101-68-8	4,4'-methylenediphenyl diisocyanate	
•	shold Limit Value established by ACGIH)	
None of the	e ingredients is listed.	
· NIOSH-Ca	a (National Institute for Occupational Safety and Health)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
	e ingredients is listed.	
· Canada		
	Domestic Substances List (DSL)	
All ingredie	ents are listed.	
Canadian	Ingredient Disclosure list (limit 0.1%)	
Janadian		

Printing date 08.08.2013

Revision: 08.08.2013

(Contd. of page 11)

#### Trade name: Seal-Krete Surface - Shell Part B

#### · Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This into	prmation is based on our present knowledge. However, this shall not constitute a guarantee f
	cific product features and shall not establish a legally valid contractual relationship.
	nt phrases
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319 H332	Causes serious eye irritation.
H332 H334	Harmful if inhaled.
H335	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
R20	Harmful by inhalation.
	38 Irritating to eyes, respiratory system and skin.
R42/43	May cause sensitisation by inhalation and skin contact.
GHS: Glod ACGIH: A EINECS: I ELINCS: I CAS: Che NFPA: Na HMIS: Ha WHMIS: V DNEL: De PNEC: Pr LC50: Let D50: Let SOS Pre	epared by:
ChemTe	
	orth Florida Avenue
	Florida USA 33602-2902
Toll Free	e North America 1-888-255-3924 Intl. +01 813-248-0573
	: www.chemtelinc.com