Printing date 17.03.2014 Revision: 03.16.2015

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Seal-Krete High Performance Epoxy Shell WB250 Part B
- Article number: 510001, 518001, 519001, 521001, 522001, 524001, 525001, 541001, 544001, 547001, 55001, 552001, 553001, 555001, 557001, 558001, 559991, 560001, 521808, 550801, 559898, 560808
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Seal-Krete / Clayton Corporation 306 Gandy Road Auburndale, FL 33823 Phone: 863-967-1535

Toll-Free: 1-800-323-7357



ChemTelInc.

(800)255-3924, +1 (813)248-0585



2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.



health hazard

H341 Suspected of causing genetic defects. Muta. 2



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn: Harmful

Possible risk of irreversible effects. R68:

Xi; Irritant

R36/38: Irritating to eyes and skin.



Xi; Sensitising

R43: May cause sensitisation by skin contact.

(Contd. on page 2)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 1)



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).







GHS07 GHS08 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) 2,3-epoxypropyl o-tolyl ether

Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P273 Avoid release to the environment. P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P201 Obtain special instructions before use.

(Contd. on page 3)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 2)

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Specific treatment (see on this label).

P321 Specific treatment (see on this label).
P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- · Hazard description:
- · WHMIS-symbols:

D2B - Toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- Indicates a long term health hazard from repeated or prolonged exposures.
- · HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 4)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

	(Cont	td. of page
Dangerous components:		
	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Xi R36/38; Xi R43; N R51/53 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	40-709
CAS: 29911-27-1	Dipropylene glycol n-propyl ether Xi R36/38 ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	20-40
CAS: 2210-79-9 EINECS: 218-645-3 Index number: 603-056-00-X	2.3-epoxypropyl o-tolyl ether Xn R68; Xi R38; Xi R43; N R51/53 Muta. Cat. 3 Muta. 2, H341 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	5-10%

4 First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not pull solidified product off the skin.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Irritant to skin and mucous membranes.

Irritant to eyes.

Gastric or intestinal disorders.

Nausea

Coughing

Dizziness

Breathing difficulty

· Hazards

Danger of impaired breathing.

Danger of convulsion.

No further relevant information available.

(Contd. on page 5)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 4)

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

Vapours may cause drowsiness and dizziness.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), 2,3-epoxypropyl o-tolyl ether. May produce an allergic reaction.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Cool endangered receptacles with water fog or haze.

Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Pick up mechanically.

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 6)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 5)

7 Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not required under normal conditions of use.

For spills, respiratory protection may be advisable.

Use suitable respiratory protective device when aerosol or mist is formed.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

(Contd. on page 7)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

· Protection of hands:

(Contd. of page 6)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information. No further relevant information available.

9 Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Clear
• Odour: Mild

Odour threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.

- Flash point:
- Flammability (solid, gaseous):
- Auto/Self-ignition temperature:

Not Determined.

206 °F / 97 °C

Not applicable.

(Contd. on page 8)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 7)

• Decomposition temperature: Not determined.

· **Self-igniting:** Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapour pressure:
Not determined.

1,094 g/cm³
Relative density
Not determined.
Vapour density
Not determined.
Evaporation rate
Not determined.

· Solubility in / Miscibility with

water: Fully miscible.Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 27 % wt (270 g/L)

 VOC (US EPA Method 24)
 27 % wt (270 g/L)

• 9.2 Other information No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Exothermic polymerization.

Reacts with catalysts, oxidizing agents and strong alkali.

Reacts with strong acids.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

(Contd. on page 9)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 8)

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitization:

Sensitization possible through skin contact.

Sensitizing effect through inhalation is possible by prolonged exposure.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

- · Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.
- · Sensitisation: Sensitization possible by skin contact.
- · Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Muta. 2

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

Toxic for fish

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 10)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 9)

• 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

> Not Regulated UN3082

Not Regulated

tolvl ether)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· 14.1 UN-Number

· DOT · ADR. IMDG. IATA

· 14.2 UN proper shipping name

· DOT

· ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number

· IMDG, IATA

· 14.3 Transport hazard class(es)

· DOT

· Class Not Regulated

· ADR



· Class

9 (M6) Miscellaneous dangerous substances and articles.

average molecular weight ≤ 700), 2,3-epoxypropyl o-

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), 2,3-epoxypropyl o-tolyl ether)

(Contd. on page 11)

(Contd. of page 10)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

· Label 9

· IMDG, IATA

• Class 9 Miscellaneous dangerous substances and articles.

· Label

· 14.4 Packing group

· **DOT** Not Regulated

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: Yes

Special marking (ADR):
Special marking (IAT A):

Symbol (fish and tree)
Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and

articles.

Danger code (Kemler): 90EMS Number: F-A,S-F

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

• UN "Model Regulation": UN3082, ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), 2,3-epoxypropyl o-

tolyl ether), 9, III

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 12)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 11)

· Proposition 65 (California):

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic Categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Canada

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

(Contd. on page 13)

Printing date 17.03.2014 Revision: 03.16.2015

Trade name: Epoxy Shell WB250 Part B

(Contd. of page 12)

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R68 Possible risk of irreversible effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 2: Germ cell mutagenicity, Hazard Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com