

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B**

Article number:

231803, 231805, 232805, 221805, 982801, 982802, 982803, 982804, 982805, 982806, 982807, 982808, 982809, 982810, 982811, 982812, 982813, 982814, 982815, 982816, 982899
231003, 231005, 982001, 982002, 982003, 982004, 982005, 982006, 982007, 982008, 982009, 982010, 982011, 982012, 982013, 982014, 982015, 982016, 982999

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Protective coating

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Seal-Krete / Clayton Corporation
306 Gandy Road
Auburndale, FL 33823
Phone: 863-967-1535
Toll-Free: 1-800-323-7357



1.4 Emergency telephone number:

ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H312 Harmful in contact with skin.
Acute Tox. 4 H332 Harmful if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



C; Corrosive

R34: Causes burns.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 1)

 Xn; Harmful

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

 Xi; Sensitising

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Benzyl alcohol

Cycloaliphatic Amine Adduct

· **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P280 Wear protective gloves / eye protection.

P260 Do not breathe mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 2)

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P310 Immediately call a POISON CENTER/doctor.


P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Hazard description:**

- **WHMIS-symbols:**

D2B - Toxic material causing other toxic effects

E - Corrosive material



- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **HMIS Long Term Health Hazard Substances**

None of the ingredients is listed.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9	3-aminomethyl-3,5,5-trimethylcyclohexylamine C R34; Xn R21/22; Xi R43 R52/53 <hr/> Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
---	--	--------

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

		(Contd. of page 3)
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5	Benzyl alcohol ☒ Xn R20/22 ☠ Acute Tox. 4, H302; Acute Tox. 4, H332	25-50%
	Cycloaliphatic Amine Adduct ☠ C R34; ☒ Xn R20/21/22; ☒ Xi R43 R52/53 ☠ Skin Corr. 1B, H314 ☠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	10-25%
<p>· Additional information: For the wording of the listed risk phrases refer to section 16.</p>		

4 First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately rinse with water.

If skin irritation continues, consult a doctor.

Seek immediate medical help for blistering or open wounds.

· **After eye contact:**

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Allergic reactions

Breathing difficulty

Cramp

Coughing

Nausea

Gastric or intestinal disorders when ingested.

Strong caustic effect on skin and mucous membranes.

· **Hazards**

Danger of gastric perforation.

Danger of severe eye injury.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 4)

Danger of disturbed cardiac rhythm.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, Cycloaliphatic Amine Adduct. May produce an allergic reaction.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

Medical supervision for at least 48 hours.

5 Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** None.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information**

Use large quantities of foam as it is partially destroyed by the product.

Eliminate all ignition sources if safe to do so.

6 Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Clean the affected area carefully; suitable cleaners are:

Warm water

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

See Section 13 for disposal information.

(Contd. of page 5)

7 Handling and storage

- **7.1 Precautions for safe handling**
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
When heated the product forms flammable fumes.
Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
Unsuitable material for receptacle: aluminium.
Unsuitable material for receptacle: steel.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Do not store together with oxidizing and acidic materials.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from humidity and water.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

100-51-6 Benzyl alcohol

WEEL (USA) | Long-term value: 10 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 6)

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Contact lenses should not be worn.



Safety glasses

· **Body protection:** Alkaline resistant protective clothing

· **Limitation and supervision of exposure into the environment**

No further relevant information available.

· **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Colour:

Light yellow

· **Odour:**

Light

· **Odour threshold:**

Not determined.

· **pH-value:**

Alkaline

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 7)

- **Change in condition**
 - Melting point/Melting range:** Not Determined.
 - Boiling point/Boiling range:** 401 °F / 205 °C
- **Flash point:** 213 °F / 101 °C (PMCC)
- **Flammability (solid, gaseous):** Not applicable.
- **Auto/Self-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapour pressure at 20 °C:** 0,02 mmHg
- **Density at 20 °C:** 1,04 g/cm³
- **Relative density:** Not determined.
- **Vapour density:** 5,88 (AIR = 1)
- **Evaporation rate:** < 1 (WATER = 1)
- **Solubility in / Miscibility with water:** Soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **9.2 Other information:** No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 - Exothermic reaction with acids.
 - Reacts with oxidizing agents.
 - Reacts with halogenated compounds.
 - Corrosive action on metals.
 - Toxic fumes may be released if heated above the decomposition point.
 - Flammable vapour-air mixtures may develop if stored in large receptacles and above room temperature.
- **10.4 Conditions to avoid**
 - Store away from oxidizing agents.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 8)

- Keep ignition sources away - Do not smoke.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NO_x)
 - Ammonia

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1030 mg/kg (rat)
------	------	------------------

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
------	------	------------------

Dermal	LD50	2000 mg/kg (rabbit)
--------	------	---------------------

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Corrosive
Irritant
Danger through skin adsorption.
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
Toxic and/or corrosive effects may be delayed up to 24 hours.
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.
- **Acute effects (acute toxicity, irritation and corrosivity):** Vapours have narcotic effect.
- **Repeated dose toxicity:** Repeated exposures may result in skin and/or respiratory sensitivity.

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

100-51-6 Benzyl alcohol

LC50	460 mg/l (pimephales promelas)
------	--------------------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 9)

- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
 Avoid transfer into the environment.
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach sewage water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms
 Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
 Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
 Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN2289
- **14.2 UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

- **DOT** Isophoronediamine, mixture
- **ADR** 2289 ISOPHORONEDIAMINE, mixture

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 10)

· **IMDG, IATA** ISOPHORONEDIAMINE, mixture
 · **14.3 Transport hazard class(es)**

· **DOT**

· **Class** 8 Corrosive substances.
 · **Label** 8

· **ADR**

· **Class** 8 (C7) Corrosive substances.
 · **Label** 8

· **IMDG, IATA**

· **Class** 8 Corrosive substances.
 · **Label** 8
 · **14.4 Packing group**
 · **DOT, ADR, IMDG, IATA** III
 · **14.5 Environmental hazards:**
 · **Marine pollutant:** No
 · **14.6 Special precautions for user** Warning: Corrosive substances.
 · **Danger code (Kemler):** 80
 · **EMS Number:** F-A,S-B
 · **Segregation groups** Alkalis
 · **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **ADR**

· **Limited quantities (LQ)** 5L
 · **Transport category** 3
 · **Tunnel restriction code** E
 · **UN "Model Regulation":** UN2289, ISOPHORONEDIAMINE, mixture, 8, III

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 11)

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 355 (extremely hazardous substances):
--

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):
--

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic Categories

· EPA (Environmental Protection Agency)
--

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Canada

· Canadian Domestic Substances List (DSL)
--

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine
-----------	--

100-51-6	Benzyl alcohol
----------	----------------

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

(Contd. of page 12)

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R20/22 Harmful by inhalation and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

(Contd. on page 14)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 23.04.2014

Revision: 23.04.2014

Trade name: Seal-Krete HP Epoxy-Shell 1000 Various Colors Part B

Website: www.chemtelinc.com

(Contd. of page 13)