



# CLEAR NON-SLIP ADDITIVE

## PRODUCT DESCRIPTION

SEAL-KRETE® Clear Non-Slip Additive is an ultra-durable, micronized polymeric aggregate developed for use as an anti-skid additive in 2-part high-solids coatings such as Poly-Shell, Epoxy-Shell or Dura-Shell. Because it's a lightweight, 60-mesh, polymeric grit, SEAL-KRETE Clear Non-Slip Additive remains suspended longer. It adds non-slip texture that increases durability and abrasion resistance of floor coatings. SEAL-KRETE Clear Non-Slip Additive can be used in 2-part water-based or solvent-based urethane, polyaspartic or epoxy coatings.

## FEATURES AND BENEFITS

- For use with Poly-Shell, Epoxy-Shell and Dura-Shell
- Extremely durable, polymeric aggregate
- Chemical & solvent resistant
- Improves traction and durability
- Great for use with clear or pigmented coatings

## MIXING AND APPLICATION

If applying more than one coat, add Clear Non-Slip Additive to the topcoat only. Add to part A while mixing at lowest speed for 2 minutes. Then follow the MIXING AND APPLICATION instructions for the system you are using. A 2 oz scoop is included in the package.

## MIX ADDITIVE QUANTITY (BY VOLUME)

System	Maximum Grip	Medium Grip	Light Grip
Poly-Shell	2.0 oz/gal	1.5 oz/gal	1.0 oz/gal
Dura-Shell	2.0 oz/gal	1.5 oz/gal	1.0 oz/gal
Epoxy-Shell	4.5 oz/gal	3.0 oz/gal	2.0 oz/gal

## LIMITATIONS

SEAL-KRETE Clear Non-Slip Additive is not recommended for repellents, silicones, wax-based coatings or 1-part floor paints, stains and sealers.

**CAUTIONS:** Use with adequate ventilation. Use appropriate, properly fitted respiratory protection filter apparatus and avoid breathing dust and particles.

**FIRST AID:** If you experience dizziness, headache or eye watering, get to fresh air; leave the area. In case of eye contact, flush with large amounts of water. Get medical attention if irritation persists. Do not take internally. If swallowed, get medical attention immediately. See Material Safety Data Sheet for additional information.

**KEEP OUT OF REACH OF CHILDREN.**

Product	No.	Unit	UPC Code	Carton Bar Code	Carton Size (W x D x H)	Cube / Wt. (cubic ft / lbs)	Carton Qty	Pallet Qty
Clear Non-Slip Additive	404001	5 lb. box	0 15944 40401 2	-	14.38 x 7.75 x 8.5	.55 / 12.32	-	-

**LIMITED WARRANTY:** Manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price. Convenience Products will not be responsible for labor or the cost of labor for removal or application of any product.

**TECHNICAL SUPPORT:** For more information on surface prep or application guidelines, or to obtain a Material Safety Data Sheet, call 1-800-323-7357, M-F (8:00 am – 5:00 pm EST) or visit our website at [www.hp.seal-krete.com](http://www.hp.seal-krete.com).

Country of Origin: U.S.A.



11 Hawthorn Pkwy., Vernon Hills, IL 60061  
800-323-3584 [rustoleum.com/seal-krete](http://rustoleum.com/seal-krete)

**HOW TO TREAT CONCRETE**

[hp.seal-krete.com](http://hp.seal-krete.com)

SK64067 0517